50MM ROCKWOOL BACKING 40MM RYANFIRE HP-X 90MM PLT FLOOR THE ANNULAR GAP. ENSURE THE GAP IS COMPLETELY POLYBUTYLENE PIPES

Approval: AS 1530.4/4072.1 87

BK: Ref: PF 20061

ID:

Products:

Scenario: Penetration seal to polybutylene

RYANFIRE HP-X

pipes

Services: Up to Ø28mmm polybutylene

pipes

Annular: 9mm — 14mm

90mm PLT floor Construction:

Fire Integrity: 60 minutes Fire Insulation: 60 minutes

Web based drawings are for example only, fire performance of any system is dependant on, but not limited to size of opening, substrate, if penetrations are passing through, type, size and number. Please refer to Ryanfire technical department for detailed and specific fire performance information.



Client

Job Title

Ryanfire HP-X to polybutylene pipes **Parallel Laminated Timber floor**

Scale	Date	
NTS	November 2020	
Sheet Size	Drawn By	
A3		
Drawing Number		Rev
V23.5		1.0

Please note: Ryanfire Products Ltd owns and has copyright in these drawings. They are to be used only for the purpose for which they were intended and supplied and are not to be sold, transferred or made available for use by a third party.

Any misuse of these drawings will result in legal proceedings.

INSTALLATION INSTRUCTIONS

DUST AND DEBRIS.

PIPE.

FILLED.

1. ENSURE THE APERTURE IS CLEAN AND FREE OF ANY

2. INSERT A 50MM DEEP ROCKWOOL BACKING INTO

THE ANNULAR GAP AROUND THE POLYBUTYLENE

APPLY RYANFIRE HP-X TO A DEPTH OF 40MM INTO

4. REMOVE ANY EXCESS HP-X WITH A DAMP CLOTH.

All errors and omissions excepted - the Information contained within this drawing is believed to be correct on the date of publication, and is based upon tested and certified solutions. The policy of RyanFire Products Ltd is one of constant improvement. Installers must therefore ensure that they are following the latest published drawings, test evidence and instructions. Whilst RyanFire Products Ltd will endeavour to keep its publications up to date, the accuracy of the information contained within this drawing may be affected by pertinent changes in the law or regulatory requirements and alterations or amendments to the specification of the manufactured products. Terms and conditions of sale apply.

RYANFIRE Technical Support: info@ryanfire.co.nz - Tel 09 443 0362