75MM SCREWS 20MM RYANFIRE HP-X RYANFIRE SL32 COLLAR 90MM PLT FLOOR KELOX PIPES

Products:

RYANFIRE SL COLLAR

RYANFIRE HP-X

Approval:

AS 1530.4/4072.1

BK:

Ref:

PF 20061

ID:

Scenario:

Penetration seal to KELOX pipes

Services:

Up to Ø32mm KELOX pipes

Annular:

0-8mm

Construction:

90mm PLT floor

Fire Integrity: 30 minutes

Fire Insulation: 0 minutes

Web based drawings are for example only, fire performance of any system is dependant on, but not limited to size of opening, substrate, if penetrations are passing through, type, size and number. Please refer to Ryanfire technical department for detailed and specific fire performance information.



Client

Job Title

Ryanfire SL Collar to KELOX pipes **Parallel Laminated Timber floor**

Scale	Date	
NTS	November 2020	
Sheet Size	Drawn By	
A3		
Drawing Number		Rev

Any misuse of these drawings will result in legal proceedings.

All errors and omissions excepted - the Information contained within this drawing is believed to be correct on the date of publication, and is based upon tested and certified solutions. The policy of RyanFire Products Ltd is one of constant improvement. Installers must therefore ensure that they are following the latest published drawings, test evidence and instructions. Whilst RyanFire Products Ltd will endeavour to keep its publications up to date, the accuracy of the information contained within this drawing may be affected by pertinent changes in the law or regulatory requirements and alterations or amendments to the specification of the manufactured products. Terms and conditions of sale apply.

RYANFIRE Technical Support: info@ryanfire.co.nz - Tel 09 443 0362

V22.24

Ryanfire Products Ltd owns and has copyright in these drawings. They are to be used only for the purpose for which they were intended and supplied and are not to

INSTALLATION INSTRUCTIONS

DUST AND DEBRIS.

THE KELOX PIPE.

THE FLOOR.

ARE USED.

FILLED.

1. ENSURE THE APERTURE IS CLEAN AND FREE OF ANY

APPLY RYANFIRE HP-X TO A DEPTH OF 20MM INTO THE ANNULAR GAP. ENSURE THE GAP IS COMPLETELY

SELECT THE RYANFIRE SL32 COLLAR TO FIT AROUND

4. FIT THE SL32 COLLAR AROUND THE PIPE AND SLIDE IT UP UNTIL IT IS FLUSH TO THE BOTTOM SURFACE OF

5. SECURE THE SL32 COLLAR TO THE FLOOR WITH 75MM TIMBER SCREWS. ENSURE ALL FIXING POINTS

6. REMOVE ANY EXCESS HP-X WITH A DAMP CLOTH.

be sold, transferred or made available for use by a third party.

1.0